

GOLDRING



EST. 1906

Goldring Elite Cartridge



The Elite is an ultra high-performance low-output moving coil cartridge which incorporates all of Goldring's most time-honoured design features. These include advanced magnetic circuitry with neodymium magnet and an ultra-rigid Pocaan® body. The Elite incorporates a Gyger S line-contact nude diamond stylus, providing maximum groove information retrieval and an outstandingly smooth and extended frequency response. The Swedish iron armature is hand-wound with pure silver wire which provides much higher definition than is found in standard record cartridge construction.

The Elite represents the very best in traditional British audio technology and design.

GOLDRING



EST. 1906

Features

Frequency Response: 20 Hz-30 kHz +/- 2 dB

Channel Balance: within 1 dB @ 1 kHz

Channel Separation: better than 25 dB @ 1 kHz

Sensitivity: 0.5 mV +/- 1 dB @ 1 kHz

Static Compliance: 18 mm/N

Equivalent tip mass: 0.35 mg

Vertical Tracking Angle: 20 °

Stylus Radius: Gyger S

Stylus Type: Non-Replaceable

Load Resistance: 100 Ω

Load Capacitance: 100 - 500 pF

Internal Inductance: 2 μ H

Internal Resistance: 8 Ω

Cartridge Mass: 5.7 g

Cartridge Mass (inc. fixings): 6.6 g

Fixing Centre: 0.5 " (12.7 mm)

Playing Weight: 1.5 - 2.0 g (1.7 g nom.)

GOLDRING



EST. 1906

Goldring Elite Stylus

A Gyger S line-contact nude diamond stylus, providing maximum groove information retrieval and an outstandingly smooth and extended frequency response.

Features

Stylus Radius: Gyger S

Stylus Type: Non-Replaceable